

HONDEX®


Wideband Echo Sounder

HE-7300-WB-Bo

HE-1511-WB-Bo

Performance Driven Equipment for Commercial Fishing

Wideband Frequency Capability



Wideband Echo Sounder

HE-7300-WB-Bo

10.4"
model

HE-1511-WB-Bo

15"
model

FROM **1KW** UP TO **5KW**

**OUTPUT
POWER**

FROM **28KHZ** UP TO **220KHZ**

FREQ.

Supporting
New Wideband Transducer
TD360 , TD380 , TD390

HE-7300-WB-Bo / HE-1511-WB-Bo

■ Specifications

Display	10.4" Color TFT LCD (7300-WB) / 15" Color TFT LCD (1511-WB)
Number of Pixel	640 X 480(7300-WB) / 1024 X 480(1511-WB)
Operating Voltage	11-30V DC
Power Consumption	24W (7300-WB) / 36W (1511-WB)
Display Style	Portrait, Landscape
Weight	Approx. 4kg (7300-WB) / Approx. 7kg (1511-WB)
Output Power	1 to 5kW (Depending on the transducer)
Frequency	Dual frequency from 28 up to 220kHz To use other freq., please ask your dealer.
Depth Range	0 to 2,000 Meters / Fathoms 0 to 6,000 Feet
Max Shift Range	2,000 to 4,000 Meters / Fathoms 6,000 to 8,000 Feet
Auto Range / Auto Shift	OFF / Range / Shift
Auto Gain	OFF / Low / High
A-Mode	OFF / ON
Fish Alarm	OFF / Small / Large
Water Temp. Alarm	OFF / In Range / Out Range (Optional water temp. sensor required)
Depth Alarm	OFF / In Range / Out Range
Expansion Mode	OFF / BL / Auto / Manual
Expansion Rate	X2, X4, X8
Background Color	4 Colors
Color Configuration	5 Patterns
Depth Unit	Meters / Feet / Fathoms
Depth Readout	S / M / L
Scale Line	OFF / ON
Super Range	OFF / ON
Clean Echo	OFF / L / M / H
STC	L / M / H
TX Power	OFF / Low / High
NMEA Output	Depth (DBT sentence) Water Temp. (MTW sentence)

■ In the Box

- Main Unit
- Power Supply Cable (DC07)



DC07

■ Optional Accessories

- Thru-hull Water Temp. Sensor : TC02CS (8P-15m) + TCK01
- Transom Water Temp. Sensor : TC03-05 (8P-5m)
- Transom Water Temp. Sensor : TC03-10 (8P-10m)
- Front Cover : CV02 (for 10.4")



TC02CS



TCK01



TC03-05



CV02

Wideband Transducer



TD360

(2kW 38-70kHz + 1kW 130-220kHz)



TD380

(3kW 38-70kHz + 1kW 130-220kHz)

TD390

(5kW 38-70kHz)


Traditional Transducer

 Depth Range
Unit: Meters

Output Power	Freq. (kHz)	40/75	50	200	50&200	32/40	36/65	28	28/55/100
1kW					TD47(T)				
1.5kW		TD51	TD30	TD33	TD66				
2kW	1.8kW				TD67T				
					TD68				
2.5kW		TD73				TD70			
3kW		TD83	TD113	TD89		TD80	TD81	TD88	TD87
5kW		TD93					TD95		TD97


Dimension (HE-7300-WB-Bo)

Unit: mm



Dimension (HE-1511-WB-Bo)

Unit: mm



Specifications are subject to change without notice.

● Dealer



HONDA ELECTRONICS CO., LTD.

 20 Oyamazuka, Oiwa-cho,
Toyohashi, Aichi 441-3193, Japan
TEL: +81-532-41-2512

<https://www.honda-el.co.jp/en/marine/>


HONDEX® is the registered trademark of HONDA ELECTRONICS CO.,LTD. in the United States, Japan and other countries.

29 SEP 2020